



# Shanghai Sunpace Machinery Co., Ltd.



26.378 Inch | 670 Millimeter x 38.583 Inch | 980 Millimeter x 9.055 Inch | 230 Millimeter TIMKEN 230/670KYMBW507C08 Spherical Roller Bearings

Bearing No. 230/670KYMBW507C08

230/670KYMBW507C08 Bearing 2D drawings and 3D CAD models

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	579.237
EAN	0087796245198
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH30/670 (Specify bore)
Inch - Metric	Metric
Long Description	670MM Tapered Bore; 980MM Outside Diameter; 230MM Width; C0-Medium Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable; Adapter Part
Other Features	Order adapter or



## Shanghai Sunpace Machinery Co., Ltd.

	withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	230/670 KYMBW507C08
Weight / LBS	1,277
Adapter Part Number	SNW30670 (Specify bore) Inch   H30/670HG (Specify bore) Millimeter
d	26.378 Inch   670 Millimeter
D	38.583 Inch   980 Millimeter
B	9.055 Inch   230 Millimeter
Design Unit	METRIC
Bore Taper	1/12
Bearing Weight	596.000 Kg
Cage Type	YMB
UPC Code	087796245198
d - Bore	670.000 mm
D - Outer Diameter	980.000 mm
B - Inner Ring Width	230 mm
B - Outer Ring Width	230.000 mm
R - Inner Ring To Clear Radius <sup>1</sup>	6.000 mm
r - Outer Ring To Clear Radius <sup>2</sup>	6.000 mm
da - Inner Ring Backing Diameter	744.000 mm
Da - Outer Ring Backing Diameter	911.000 mm
C0 - Static Radial Rating	15800000 N



## Shanghai Sunpace Machinery Co., Ltd.

C1(2) - Dynamic Radial Rating (Two-Rows)	7890000 N
e - ISO Factor <sup>3</sup>	0.22
Y0 - ISO Factor <sup>4</sup>	3.12
Y1 - ISO Factor <sup>5</sup>	4.65
Y2 - ISO Factor <sup>6</sup>	3.05
Reference Thermal Speed Rating (Grease)	330
Reference Thermal Speed Rating (Oil) <sup>7</sup>	380
Cg - Geometry Factor <sup>8</sup>	0.1257